

## Cold Holdings

## 25" Cold Holding Refrigerator SKDL25-ESUS2

Specification Sheet



### **Features**

#### **Eco-Friendly Refrigerant**

R290 refrigerant with a global warming potential (GWP) of 3

#### **High-Strength Door**

Heavy-duty, stainless steel door is assembled using high-load brackets for long lasting durability

#### **Easy to Clean**

Stainless steel interior, coved corners, finished edges

#### **Stainless Steel Exterior**

Galvanized back and stainless steel bottom to reduce the risk of corrosion

#### **High-Density Insulation**

Foamed-in-place, CFC-free polyurethane insulation for maximum strength, rigidity, and insulation

#### **Cold Wall Refrigeration System**

Optimized temperature control thanks to the cold wall refrigeration

#### **Front Access Dispense Point**

Includes a wide, front-access flapper door for easy access to fresh produce while maintaining an optimal holding environment

#### **Cabinet Capacity**

Internal area of 4.7ft<sup>3</sup> with one product bin with removeable lid and front access door

#### Versatility


Standard countertop design includes optional wall mount accessory to free up counterspace





# Cold Holdings 25" Cold Holding Refrigerator SKDL25-ESUS2

Specification Sheet



#### **Technical Specifications**

Electrical Requirements	115v/60hz/1ph/3A/NEMA 5-15P Plug
Product Dimensions	25.6"W x 36.27"H x 23.57"D (65.02cm x 92.13cm x 59.87cm)
Product Weight	130lbs (58.97kg)
Shipping Dimensions	31"W x 45"H x 32"D (78.74cm x 114.30cm x 81.28cm)
Shipping Weight	145lbs (65.77kg)
Shipping Cubic Dimensions	25.83ft <sup>3</sup> (0.73m <sup>3</sup> )
Refrigerant	R290
Charge Level	1.9oz (53.9 grams)

Temperature Range	36 to 40 (2.2 to 4.4°C)
Insulation	Foamed-in-place, CFC-free polyurethane
Exterior Construction	Stainless steel exterior with galvanized back and bottom
Interior Construction	Stainless steel interior with coved corners and finished edges
Doors	One (1) right-hand swing door, reversible
Interior Capacity	4.7 cubic feet
Certifications	ETL Safety, ETL Sanitation
Warranty	3-year parts and labor, 5-year compressor (part only)

Model Number	Description
SKDL25-ESUS2	Cold holding Refrigerator 25", 115v/60hz/1ph, single right-hand swing door, product bin, NEMA 5-15P

To learn more about Cold Holding Refrigerator, visit silverking.com

